


Submittal: SDPRW1023W



STRONG-POINT[®] PHILLIPS WAFER HEAD w/WINGS, WAR COATED

Size	Part#	Pt.	Case Qty.	Wood Attach. Range	Description
10-24 x 1-7/16	R107W	3	4M	1/4" - 3/4"	Phillips Wafer Head w/Wings, WAR Coated

Application: Attaches plywood to metal.
Drill Capacity (in.): .035 - .176

- Specifications:
- Meets ASTM¹ C 1513 for cold-formed steel framing connections
 - Meets ASTM A 510 for carbon steel manufacturing
 - Manufactured to SAE² J78 for dimensional specifications
 - Meets F.I.P.³-1000.7 for torsional strength and drill speed

- Features:
- WAR coating exceeds 1,000/hr. salt spray resistance
 - Designed to work with ACQ, pressure, and fire treated lumber
 - Wings ream hole in wood preventing "jacking action"



Installation: A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 Phillips drive bit. Do not over torque as it can cause the head to snap or stripping of the recess. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)									
Fastener		Steel Gauge							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
10-24	3		335	496	702	901	1469	2112	2668

Shear Values (Avg. Lbs.)									
Fastener		Steel Gauge (Lapped)							
Size	Pt.	22	20	18	16	14	12	1/8	3/16
10-24	3		709	1231	1497	1508			

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

¹(American Society of Testing Materials)

²(Society of Automotive Engineers)

³(Fastener Inspection Products)

R107W_Rev. A (4/4/25)